



SWIFT. SILENT. SECURE.

Spacer for Side Mount Adapter Plate

(For BMS Jack Plates)

INCLUDED HARDWARE:

A (1) Spacer

INSTALLATION TOOLS:

- 3/4" Socket with Ratchet
- 3/4" Wrench

STEP 1 Locate the pre-drilled holes underneath the Decal Stickers **FIG. 1** If holes are found, skip to **STEP 4**.

If you are unable to find the pre-drilled holes, use the Drill Measurement Guide

(Bob's Machine Shop) in the Side Mount Adapter Plate Bolt Set Instructions.

STEP 2 Check on the inside of the Jack Plate where holes are being drilled for any obstructions or clearance issues when installing hardware.

NOTE: Bolts and Hardware are not included with **Spacer (A)**.

STEP 3 Drill a 1/2" hole into each of the marked hole locations.

STEP 4 Place **Spacer (A)** over the recessed area, aligning the holes in **Spacer (A)** with those in the Jack Plate.

IMPORTANT! For some Jack Plate models, Spacer (A) will SPAN, NOT FIT INTO the recessed area.

STEP 5 Finish by following the Side Mount Adapter Plate Bolt Set instructions specific to your Jack Plate.

NOTE: JL Marine Systems, Inc. recommends that adapter plates be installed by an authorized Power-Pole® dealer. To find a dealer near you go to power-pole.com



Figure 1

Need help? Contact our Customer Service Team at **1 + 813.689.9932 Option 2**



9010 Palm River Road, Tampa, Florida 33619
phone 813.689.9932 fax 813.689.8883 • power-pole.com
©2020 all rights reserved. Power-Pole Shallow Water Anchor U.S. Patent No. 6,041,730